250 liter tank i Rostfritt 304



45 000 SEK /st exkl moms

Article type: second-hand pressure tank
Additional information: Top lid is missing, a new lid = 650 €.
There are two connections provided with 2 inch internal thread for mounting 2 immersion resistors with an insertion length of 500mm, the immersion resistors themselves are not included.
Volumetric volume (L): 250 L
Pressure in tank: pressure
Design pressure (Bar): 5,20 Bar

Max. pressure (Bar): 3,50 Bar
Max. temperature (°C): 100 °C
Material wet parts: SS AISI 304L (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical
Configuration: single jacketed with heat-exchanger

Heat exchanger: yes
Insulation: no
Mobile tank: no
Top type: dished
Shape of tank: cylindrical

Bottom type: dished
Total discharge: yes
Fixation points: on skirt
Type of HE on the cylinder: atmosfertical double jacket
Type of HE on the bottom: atmosfertical double jacket

Heat exchanger: RVS 304
Fixation point(s): RVS 304
Suitable for food industry: no
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 355 mm

Tank outlet: inside Ø 32 mm
Outlet type: bsp female
Agitator: no, optional
Internal diameter tank: 695 mm
Distance from outlet to ground: 400 mm

Outer diameter tank: 795 mm
Cylinder height: 560 mm
Total height of tank: 1.370 mm
Empty weight tank: 300

SKU: 383153

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Designtryck för tanken: 5,20 Bar
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Top lid is missing, a new lid = 650 €. There are two connections provided with 2 inch internal thread for mounting 2 immersion resistors with an insertion length of 500mm, the immersion
Övrig information2: resistors themselves are not included.
Omrörare: Nej
Övertryck: 3,50 Bar
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: dished
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304L (V2A)
Volym i liter: 250

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Tankutlopp: inside Ø 32 mm
Teknisk ritning finns: Nej
Utloppstyp: bsp female

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 560 mm
Invändig diameter: 695 mm
Mått utlopp till marken: 400 mm
Total höjd: 1.370 mm
Ytterdiameter: 795 mm

Värmeväxlare

Typ av värmeväxlare på cylinder: atmosfertical double jacket
Typ av värmeväxlare på botten: atmosfertical double jacket

Mer

Värmeväxlare: RVS 304
Isolerad: Nej
Vikt: 300