250 liter tank i Rostfritt 304



126 000 SEK /st exkl moms

Volumetric volume (L): 250 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 1 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

Mobile tank: no
Total discharge: yes
Volume: 90 L
Max Overpressure: 0,50 Bar
Max. working temperature: 110 °C

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: 48
Agitator: yes
Number of revolutions: 1420 / 2870
Power: 2.2 / 2.7

Internal diameter tank: 640 mm
Outer diameter tank: 830 mm
Cylinder height: 620 mm
Total height of tank: 2.000 mm

SKU: 489874

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: pharmacy; we can’t give any guarantees about the heating/cooling jacket; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 250

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank
Cylinderhöjd: 620 mm
Invändig diameter: 640 mm
Total höjd: 2.000 mm
Ytterdiameter: 830 mm

Omrörare
Kraft (kW): 2.2 / 2.7
Varvtal: 1420 / 2870

Mer
Isolerad: Ja