

250 liter tank i Syrafast 316



22,000,00 SEK /st exkl moms

Additional information: Chemistry; Diameter of handhole approx. 210 mm (handhole flange made of Fe); some residues of previous content

Volumetric volume (L): 250 L

Pressure in tank: vacuum

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN50

Internal diameter tank: 690 mm

Cylinder height: 570 mm

Total height of tank: 1.560 mm

SKU: 485267

Mer information



Beskrivning av produkt

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Diameter of handhole approx. 210 mm (handhole flange made of Fe); some residues of previous content

Omrörare: Nej

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Uppvärmning/kylning: Nej

Volym i liter: 250

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Dimensioner av tank

Cylinderhöjd: 570 mm

Invändig diameter: 690 mm

Total höjd: 1.560 mm

Mer

Isolerad: Nej