

2500 liter tank i Rostfritt 304



79,000,00 SEK /st exkl moms

Additional information: Original calculation overpressure of the inner tank according to technical documents 5.4 bar (test overpressure 8.2 bar); agitator in the manhole cover was probably retrofitted by the previous operator; some residues of previous content

Volumetric volume (L): 2.500 L

Pressure in tank: pressure

Max. pressure (Bar): 5,40 Bar

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 26 L

Max Overpressure: 10 Bar

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN32

Agitator: yes

Number of revolutions: 720 / 970

Power: 0.75 / 1.3



Top: 7,60 mm

Cylinder: 6 mm

Bottom: 7 mm

Internal diameter tank: 1.400 mm

Cylinder height: 1.250 mm

Total height of tank: 3.200 mm

SKU: 571865

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: Original calculation overpressure of the inner tank according to technical documents 5.4 bar (test overpressure 8.2 bar); agitator in the manhole cover was probably retrofitted by the previous

Övrig information2: operator; some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 5,40 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 2500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.250 mm

Invändig diameter: 1.400 mm

Total höjd: 3.200 mm

Omrörare

Kraft (kW): 0.75 / 1.3

Varvtal: 720 / 970

Tjocklek på tank

Botten: 7 mm

Cylinder: 6 mm

Topp: 7,60 mm

Mer

Isolerad: Nej