2500 liter tank i Rostfritt 304



81 000 SEK /st exkl moms

Additional information: Original calculation overpressure of the inner tank according to technical documents 5.4 bar (test overpressure 8.2 bar); agitator in the manhole cover was probably retrofitted by the previous operator; some residues of previous content
Volumetric volume (L): 2.500 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 5,40 Bar
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Volume: 26 L
Max Overpressure: 10 Bar
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN32
Agitator: yes

Number of revolutions: 720 / 970
Power: 0.75 / 1.3
Top: 7,60 mm
Cylinder: 6 mm
Bottom: 7 mm

Internal diameter tank: 1.400 mm
Cylinder height: 1.250 mm
Total height of tank: 3.200 mm

SKU: 571865

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single jacketed with heat-exchanger
Mobil tank: Nej
Övrig information: Original calculation overpressure of the inner tank according to technical documents 5.4 bar (test overpressure 8.2 bar); agitator in the manhole cover was probably retrofitted by the previous
Övrig information2: operator; some residues of previous content; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 5,40 Bar
Total urtappning: Yes
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 2500

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank
Cylinderhöjd: 1.250 mm
Invändig diameter: 1.400 mm
Total höjd: 3.200 mm

Omrörare
Kraft (kW): 0.75 / 1.3
Varvtal: 720 / 970

Tjocklek på tank
Botten: 7 mm
Cylinder: 6 mm
Topp: 7,60 mm

Mer
Isolerad: Nej