

2500 liter tank i Rostfritt 304



55 000 SEK /st exkl moms

Additional information: adhesive production; Frame made of Fe (with corrosion attachment); rectangular opening approx. 490 x 590 mm in the upper bottom; some residues of previous content; motor-/gear is missing

Volumetric volume (L): 2.500 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Outlet of tank: flange DN100
Agitator: yes
Internal diameter tank: 1.350 mm

Outer diameter tank: 1.440 mm
Cylinder height: 1.940 mm
Total height of tank: 3.650 mm

SKU: 269968

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: adhesive production; frame Fe (with corrosion); rectangular opening appr. 490 x 590 mm in the upper bottom; some residues of previous content; motor-/gear is missing; we can't give any guarantees

Övrig information2: about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 2500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.940 mm

Invändig diameter: 1.350 mm

Total höjd: 3.650 mm

Ytterdiameter: 1.440 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Nej
