

## 2500 liter tank i Rostfritt 304



**70 000 SEK /st exkl moms**

**Article type:** second-hand mixing tank

**Additional information:** we can't give any guarantees about the agitator

**Volumetric volume (L):** 2.500 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no



**Mobile tank:** no

**Top type:** conical

**Shape of tank:** cylindrical

**Bottom type:** conical

**Total discharge:** yes

**Fixation points:** 3 adjustable feet

**Manway(s):** RVS 304

**Gasket manway(s):** unknown

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** at the top

**Hinged lid:** yes

**Tank outlet:** inside Ø 60 mm

**Agitator:** yes

**Agitator type:** propeller agitator

**Position engine:** at the top

**Power:** 0,55

**Voltage:** 230 V - three-phase

**Current:** 2,60

**Distance from outlet to ground:** 860 mm

**Outer diameter tank:** 1.400 mm

**Cylinder height:** 1.475 mm

**Total height of tank:** 3.350 mm

**Empty weight tank:** 750

**SKU:** 294817

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 2500

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 60 mm

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304



## Dimensioner av tank

Cylinderhöjd: 1.475 mm  
Mått utlopp till marken: 860 mm  
Total höjd: 3.350 mm  
Ytterdiameter: 1.400 mm

## Omrörare

Kraft (kW): 0,55  
Position motor: at the top  
Typ av omrörare: propeller agitator  
Spänning (Volt): 230 V – three-phase

## Mer

Isolerad: Nej  
Vikt: 750