

2500 liter tank i Syrafast 316



53,000,00 kr /st exkl moms

Additional information: Chemistry; Manhole diameter approx. 460 mm; outlet probably DN 50 reduced to approx. 15 mm by flanged fitting; 2 dip pipes inside the tank

Volumetric volume (L): 2.500 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Agitator: yes

Number of revolutions: 520

Power: 2,10

Internal diameter tank: 1.390 mm

Cylinder height: 1.600 mm

Total height of tank: 5.050 mm

SKU: 490227

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Chemistry; Manhole diameter approx. 460 mm; outlet probably DN 50 reduced to approx. 15 mm by flanged fitting; 2 dip pipes inside the tank; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.600 mm

Invändig diameter: 1.390 mm

Total höjd: 5.050 mm

Omrörare

Kraft (kW): 2,10

Varvtal: 520

Mer

Isolerad: Nej
