

2500 liter tank i Syrafast 316



94 000 SEK /st exkl moms

Additional information: Manhole diameter: approx. 415 mm; Note: Manhole collar and manhole cover are made of stainless steel 304

Volumetric volume (L): 2.500 L

Pressure in tank: ATM - atmospheric



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 17 / 35

Power: 0.9 / 1.8

Internal diameter tank: 1.190 mm

Outer diameter tank: 1.300 mm

Cylinder height: 1.600 mm

Total height of tank: 3.450 mm

SKU: 705187

Mer information



Beskrivning av produkt

Material: Acid-resistant 316

Modell: Vertical

Nyttillverkad/Begagnad: Used

Arbetsstryck i tank: ATM – atmospheric

Konfiguration: single-skin

Mobil tank: No, it is not.

Övrig information: Manhole diameter: approx. 415 mm; Note: Manhole collar and manhole cover are made of stainless steel 304; we can't give any guarantees about the agitator

Omrörare: Yes

Total urtappning: Yes

Uppvärmning/kylning: No, it is not.

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2500

Utrustning

Dokument finns: No, it is not.

Fläns för omrörare: No

Märkskylt: No, it is not.

Teknisk ritning finns: No, it is not.

Översikt material

Material: Acid-resistant 316

Dimensioner av tank

Cylinderhöjd: 1.600 mm

Invändig diameter: 1,190 mm

Total höjd: 3.450 mm

Ytterdiameter: 1.300 mm

Omrörare

Kraft (kW): 0.9 / 1.8

Varvtal: 17 / 35



Mer

Isolerad: No