2500 liter tank i Syrafast 316



185 000 SEK /st exkl moms

Additional information: Support ring made of Fe; minor dents in the iso jacket; manhole cover partially plated; manhole diameter 490 mm; some residues of previous content
Volumetric volume (L): 2.500 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 180 L
Max Overpressure: 16 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 130

Agitator: yes
Number of revolutions: 307
Power: 1,10
Internal diameter tank: 1.590 mm
Outer diameter tank: 1.880 mm

Cylinder height: 1.380 mm
Total height of tank: 3.250 mm

SKU: 397889

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Chemistry; Support ring made of Fe; smaller dents in the insulation jacket; Manhole cover partially plated; diameter manhole 490 mm; some residues of previous content; we can’t give any guarantees
Övrig information2: about the heating/cooling jacket; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2500

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.380 mm
Invändig diameter: 1.590 mm
Total höjd: 3.250 mm
Ytterdiameter: 1.880 mm

Omrörare
Kraft (kW): 1,10
Varvtal: 307

Mer
Isolerad: Ja