

2500 liter tank i Syrafast 316



315 000 SEK /st exkl moms

Volumetric volume (L): 2.500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 1 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 50 L

Max Overpressure: 4 Bar

Max onderdruk: 1 Bar

Max. working temperature: 50 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN50

Agitator: yes

Number of revolutions: 18 / 35

Power: 0.44 / 0.88

Cylinder: 6 mm

Bottom: 5 mm

Internal diameter tank: 1.300 mm

Outer diameter tank: 1.455 mm

Cylinder height: 1.500 mm

Total height of tank: 3.350 mm

SKU: 279244

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 50 °C

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 1 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.500 mm
Invändig diameter: 1.300 mm
Total höjd: 3.350 mm
Ytterdiameter: 1.455 mm

Omrörare

Kraft (kW): 0.44 / 0.88
Varvtal: 18 / 35

Tjocklek på tank

Botten: 5 mm
Cylinder: 6 mm

Mer

Isolerad: Ja