

## 2500 liter tank i Syrafast 316



**323,000,00 kr /st exkl moms**

**Volumetric volume (L):** 2.500 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 1 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 50 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 50 L

**Max Overpressure:** 4 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 50 °C

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** flange DN50

**Agitator:** yes

**Number of revolutions:** 18 / 35

**Power:** 0.44 / 0.88

**Cylinder:** 6 mm

**Bottom:** 5 mm

**Internal diameter tank:** 1.300 mm

**Outer diameter tank:** 1.455 mm

**Cylinder height:** 1.500 mm

**Total height of tank:** 3.350 mm

**SKU:** 279244

---

Mer information

---