

## 2500 liter tank i Syrafast 316



**171 000 SEK /st exkl moms**

**Additional information:** Chemistry; 4 claws made of stainless steel 304; fastening screws of the manhole cover incomplete; 1 former connection in the upper bottom was welded shut by the previous operator; some residues of previous content; motor-/gear is missing

**Volumetric volume (L):** 2.500 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 1 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 190 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 35 L

**Max Overpressure:** 3 Bar

**Max. working temperature:** 190 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** flange DN50

**Agitator:** yes

**Cylinder:** 5 mm

**Bottom:** 4,60 mm

**Internal diameter tank:** 1.390 mm

**Cylinder height:** 1.500 mm

**Total height of tank:** 3.000 mm

**SKU:** 283381

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 190 °C

Mobil tank: Nej

Övrig information: Chemistry; 4 support brackets, Aisi 304; Manhole cover mounting screws incomplete; 1 former connection in the upper bottom was welded shut by the previous operator; some residues of previous

Övrig information2: content; motor-/gear is missing; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 1 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2500

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Cylinderhöjd: 1.500 mm  
Invändig diameter: 1.390 mm  
Total höjd: 3.000 mm

## Tjocklek på tank

Botten: 4,60 mm  
Cylinder: 5 mm

## Mer

Isolerad: Nej