# 2500 liter tank i Syrafast 316



172 000 SEK /st exkl moms

**Additional information**: 4 claws made of stainless steel 304; fastening screws of the manhole cover incomplete; 1 former connection in the upper bottom was welded shut by the previous operator; some residues of previous content; motor-/gear is missing
**Volumetric volume (L)**: 2.500 L
**Pressure in tank**: pressure and vacuum

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

**Max. pressure (Bar)**: 1 Bar
**Min. pressure (Bar)**: 1 Bar

**Max. temperature (°C)**: 190 °C
**Material wet parts**: SS AISI 316 (V4A)
**Model**: vertical
**Configuration**: single-skin
**Heat exchanger**: no

**Insulation**: no
**Mobile tank**: no
**Total discharge**: yes
**Volume**: 35 L
**Max Overpressure**: 3 Bar

**Max. working temperature**: 190 °C
**Type HE on the bottom**: half pipe welded onto the outside of the innertank
**Type HE on the cylinder**: half pipe welded onto the outside of the innertank
**Documents included**: no
**Technical drawing included**: no

**Registration plate on the tank**: yes
**Flange for agitator**: no
**Position of manway**: headside
**Outlet of tank**: flange DN50
**Agitator**: yes

**Cylinder**: 5 mm
**Bottom**: 4,60 mm
**Internal diameter tank**: 1.390 mm
**Cylinder height**: 1.500 mm
**Total height of tank**: 3.000 mm

**SKU:** 407429

# Mer information

**Beskrivning av produkt**

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 190 °C
Mobil tank: Nej
Övrig information: Chemistry; 4 support brackets, Aisi 304; Manhole cover mounting screws incomplete; 1 former connection in the upper bottom was welded shut by the previous operator; some residues of previous
Övrig information2: content;motor-/gear is missing; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 1 Bar
Total urtappning: Yes
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2500

**Utrustning**

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

**Översikt material**

Material: Syrafast 316

**Dimensioner av tank**
Cylinderhöjd: 1.500 mm
Invändig diameter: 1.390 mm
Total höjd: 3.000 mm

**Tjocklek på tank**
Botten: 4,60 mm
Cylinder: 5 mm

**Mer**
Isolerad: Nej

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se