

2500 liter tank i Syrafast 316



135 000 SEK /st exkl moms

Additional information: Chemistry; 4 loose stainless steel foot extensions are included in the scope of delivery; some residues of previous content; Metallic discolouration inside

Volumetric volume (L): 2.500 L

Pressure in tank: vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 75 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Top: 12 mm

Cylinder: 6 mm

Bottom: 9 mm

Internal diameter tank: 1.600 mm

Cylinder height: 1.350 mm

Total height of tank: 3.200 mm

Empty weight tank: 800

SKU: 273643

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; 4 loose foot extensions made of stainless steel are included; some residues of previous content;Metallic discolouration inside

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.350 mm
Invändig diameter: 1.600 mm
Total höjd: 3.200 mm

Tjocklek på tank

Botten: 9 mm
Cylinder: 6 mm
Topp: 12 mm

Mer

Isolerad: Nej
Vikt: 800