25000 liter tank i Rostfritt 304



185 000 SEK /st exkl moms

Additional information: Double jacket by approx. 1,800 mm of the cylinder height; manhole approx. 410 x 510 mm; small dents in the vessel and in the insulating jacket; 1 sheet metal cut-out approx. 200 mm in the center of the upper bottom (see photos); some residues of previous content; pipe end cut flush
Volumetric volume (L): 25.000 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: cylinder
Outlet of tank: 80
Internal diameter tank: 2.690 mm
Outer diameter tank: 2.850 mm
Cylinder height: 4.400 mm

Total height of tank: 4.900 mm

SKU: 427169

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Mobil tank: Nej
Övrig information: Double jacket around approx. 1.800 mm of the cylinder height; Manhole approx. 410 x 510 mm; small dents in tank and insulating jacket; 1 sheet metal cutout approx. 200 mm in the middle of the upper
Övrig information2: bottom (see photos); some residues of previous content;pipe end cut flush; we can't give any guarantees about the heating/cooling jacket
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 25000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 4.400 mm
Invändig diameter: 2.690 mm
Total höjd: 4.900 mm
Ytterdiameter: 2.850 mm

Mer
Isolerad: Ja