

25000 liter tank i Rostfritt 304



185,000,00 kr /st exkl moms

Additional information: Double jacket around approx. 1.800 mm of the cylinder height; Manhole approx. 410 x 510 mm; small dents in tank and insulating jacket; 1 sheet metal cutout approx. 200 mm in the middle of the upper bottom (see photos); some residues of previous content; pipe end cut flush

Volumetric volume (L): 25.000 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no
Total discharge: yes

Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: cylinder
Outlet of tank: 80
Internal diameter tank: 2.690 mm
Outer diameter tank: 2.850 mm
Cylinder height: 4.400 mm

Total height of tank: 4.900 mm

SKU: 306029

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: Double jacket around approx. 1.800 mm of the cylinder height; Manhole approx. 410 x 510 mm; small dents in tank and insulating jacket; 1 sheet metal cutout approx. 200 mm in the middle of the upper

Övrig information2: bottom (see photos); some residues of previous content; pipe end cut flush; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 25000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 4.400 mm

Invändig diameter: 2.690 mm

Total höjd: 4.900 mm

Ytterdiameter: 2.850 mm

Mer

Isolerad: Ja
