

25000 liter tank i Rostfritt 304



135 000 SEK /st exkl moms

Additional information: food industry; 1 tank with smaller dents in the cylinder, the other tank with stronger dents in the cylindrical part; motor data of the agitators only for one motor readable; Wall thickness of the lowest cylinder segment: 3 mm

Volumetric volume (L): 25.000 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder

Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 1.415
Power: 2,20
Top: 2,80 mm

Cylinder: 2,60 mm
Bottom: 4,80 mm
Internal diameter tank: 2.350 mm
Cylinder height: 5.330 mm
Total height of tank: 7.350 mm

Empty weight tank: 1.750

SKU: 267136

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: food industry; 1 tank with smaller dents in the cylinder, the other tank with stronger dents in the cylindrical part; motor data of the agitators only for one motor readable;

Wall thickness of the

Övrig information2: lowest cylinder segment: 3 mm; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 25000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 5.330 mm

Invändig diameter: 2.350 mm

Total höjd: 7.350 mm



Omrörare

Kraft (kW): 2,20

Varvtal: 1.415

Tjocklek på tank

Botten: 4,80 mm

Cylinder: 2,60 mm

Topp: 2,80 mm

Mer

Isolerad: Nej

Vikt: 1.750