

25000 liter tank i Rostfritt 304



210 000 SEK /st exkl moms

Additional information: Dairy; Manhole diameter appr. 410 mm; 1 dent in the insulation jacket in the transition from cylinder to upper bottom; 2 of the feet are lightly pressed into the lower bottom, the previous operator welded metal sheets on the outside for stabilization (see photos); if you are looking for an identical tank for this item, we may be able to offer you an identical tank from an external stock (without

guarantee).

Volumetric volume (L): 25.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 80

Agitator: yes

Number of revolutions: 925

Power: 1,50

Internal diameter tank: 2.590 mm

Outer diameter tank: 2.700 mm

Cylinder height: 4.650 mm

Total height of tank: 6.150 mm

SKU: 286430

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Dairy; Manhole diameter appr. 410 mm; 1 dent in the insulation jacket in the transition from cylinder to upper bottom; 2 of the feet are lightly pressed into the lower bottom, the previous operator

Övrig information2:

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 25000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 4.650 mm

Invändig diameter: 2.590 mm

Total höjd: 6.150 mm

Ytterdiameter: 2.700 mm



Omrörare

Kraft (kW): 1,50

Varvtal: 925

Mer

Isolerad: Ja