25000 liter tank i Syrafast 316



385 000 SEK /st exkl moms

Volumetric volume (L): 25.000 L
Pressure in tank: pressure
Max. temperature (°C): 55 °C
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Volume: 469 L
Max Overpressure: 3 Bar
Max. working temperature: 15 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: available
Agitator: yes
Top: 4 mm
Cylinder: 4 mm
Bottom: 4 mm

Internal diameter tank: 2.750 mm
Cylinder height: 4.000 mm
Total height of tank: 6.500 mm
Empty weight tank: 2.500

SKU: 565502

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 55 °C
Mobil tank: Nej
Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 25000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 4.000 mm
Invändig diameter: 2.750 mm
Total höjd: 6.500 mm

Tjocklek på tank
Botten: 4 mm
Cylinder: 4 mm
Topp: 4 mm

Mer
Isolerad: Ja
Vikt: 2.500