

## 25000 liter tank i Syrafast 316



**382 000 SEK /st exkl moms**

**Volumetric volume (L):** 25.000 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 55 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 469 L

**Max Overpressure:** 3 Bar

**Max. working temperature:** 15 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** available

**Agitator:** yes

**Top:** 4 mm

**Cylinder:** 4 mm

**Bottom:** 4 mm

**Internal diameter tank:** 2.750 mm

**Cylinder height:** 4.000 mm

**Total height of tank:** 6.500 mm

**Empty weight tank:** 2.500

**SKU:** 565502

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 55 °C

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 25000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

### Dimensioner av tank

Cylinderhöjd: 4.000 mm

Invändig diameter: 2.750 mm

Total höjd: 6.500 mm

**Tjocklek på tank**

Botten: 4 mm

Cylinder: 4 mm

Topp: 4 mm

**Mer**

Isolerad: Ja

Vikt: 2.500