

25000 liter tank i Syrafast 316



214 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 25.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no



Top type: conical
Shape of tank: cylindrical
Bottom type: strong conical
Total discharge: yes
Fixation points: 4 adjustable feet

Manway(s): RVS 316
Fixation point(s): RVS 304
Suitable for food industry: no
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1
Position of manway: headside
Height manhole 1 (mm): 415 mm

Tank outlet: inside Ø 100 mm
Outlet type: DIN11851
Outlet of tank: DN100
Agitator: yes
Agitator type: propeller agitator

Position engine: at the top
Power: 8.5 / 12
Voltage: 380-420 V - three-phase
Current: 25/26
Internal diameter tank: 2.899 mm

Distance from outlet to ground: 930 mm
Outer diameter tank: 2.907 mm
Cylinder height: 3.540 mm
Feet height: 1.940 mm
Total height of tank: 7.100 mm

SKU: 738613



Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfäric

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: strong conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 25000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Tankutlopp: inside Ø 100 mm

Teknisk ritning finns: Nej

Utloppstyp: DIN11851

Översikt material

Material: Syrafast 316

Fixeringspunkt(er): RVS 304



Dimensioner av tank

Cylinderhöjd: 3.540 mm

Höjd på fötter: 1.940 mm

Invändig diameter: 2.899 mm

Mått utlopp till marken: 930 mm

Total höjd: 7.100 mm

Ytterdiameter: 2.907 mm

Omrörare

Kraft (kW): 8.5 / 12

Position motor: at the top

Typ av omrörare: propeller agitator

Spänning (Volt): 380-420 V – three-phase

Tjocklek på tank

Cylinder: 4 mm

Mer

Isolerad: Nej