

25000 liter tank i Syrafast 316



384 000 SEK /st exkl moms

Volumetric volume (L): 25.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 55 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 489 L

Max Overpressure: 3 Bar

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN80 DIN 11851

Top: 4 mm

Cylinder: 4 mm

Bottom: 4 mm

Internal diameter tank: 2.750 mm

Outer diameter tank: 2.925 mm

Cylinder height: 4.000 mm

Total height of tank: 6.500 mm

Empty weight tank: 2.500

SKU: 483050

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfERIC

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 55 °C

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 25000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 4.000 mm

Invändig diameter: 2.750 mm

Total höjd: 6.500 mm

Ytterdiameter: 2.925 mm

Tjocklek på tank

Botten: 4 mm

Cylinder: 4 mm

Topp: 4 mm

Mer

Isolerad: Ja

Vikt: 2.500