

25500 liter tank i Rostfritt 304



235,000,00 kr /st exkl moms

Additional information: diary; Dented fan covers of agitators; with 1 tank the cladding panels on the agitator lantern are slightly bent; height-adjustable screws of the feet are missing (see photos); pipe end cut flush

Volumetric volume (L): 25.500 L



Pressure in tank: pressure and vacuum

Max. pressure (Bar): 0,40 Bar

Min. pressure (Bar): 0,40 Bar

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 0,40 Bar

Max onderdruk: 0,40 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 100

Agitator: yes

Number of revolutions: 16

Power: 4,40

Top: 6 mm

Cylinder: 4 mm

Bottom: 5 mm

Internal diameter tank: 2.500 mm

Outer diameter tank: 2.650 mm

Cylinder height: 5.000 mm

Total height of tank: 8.050 mm

Empty weight tank: 4.000

SKU: 286151

Mer information
