

25500 liter tank i Rostfritt 304



235 000 SEK /st exkl moms

Additional information: diary; Dented fan covers of agitators; with 1 tank the cladding panels on the agitator lantern are slightly bent; height-adjustable screws of the feet are missing (see photos); pipe end cut flush

Volumetric volume (L): 25.500 L



Pressure in tank: pressure and vacuum

Max. pressure (Bar): 0,40 Bar

Min. pressure (Bar): 0,40 Bar

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 0,40 Bar

Max onderdruk: 0,40 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 100

Agitator: yes

Number of revolutions: 16

Power: 4,40

Top: 6 mm

Cylinder: 4 mm

Bottom: 5 mm

Internal diameter tank: 2.500 mm

Outer diameter tank: 2.650 mm

Cylinder height: 5.000 mm

Total height of tank: 8.050 mm

Empty weight tank: 4.000

SKU: 286151

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated

Mobil tank: Nej

Övrig information: diary; Dented fan covers of agitators; with 1 tank the cladding panels on the agitator lantern are slightly bent; height-adjustable screws of the feet are missing (see photos); pipe end cut flush;

Övrig information2: we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 0,40 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,40 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 25500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304



Dimensioner av tank

Cylinderhöjd: 5.000 mm
Invändig diameter: 2.500 mm
Total höjd: 8.050 mm
Ytterdiameter: 2.650 mm

Omrörare

Kraft (kW): 4,40
Varvtal: 16

Tjocklek på tank

Botten: 5 mm
Cylinder: 4 mm
Topp: 6 mm

Mer

Isolerad: Ja
Vikt: 4.000