

2580 liter tank i Rostfritt 304



40 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: length of the tank without cooling unit = 2950mm; Condition of the agitator is unknown, the cooling unit does not work,; we can't give any guarantees about the agitator

Volumetric volume (L): 2.580 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: horizontal

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Shape of tank: cylindrical

Total discharge: yes

Fixation points: 4 non adjustable feet

Insulation material: PUR

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 450 mm

Tank outlet: inside Ø 50 mm

Agitator: yes

Agitator type: tripod

Position engine: at the top

Distance from outlet to ground: 180 mm

Total height of tank: 1.800 mm

Total outer width: 1.250 mm

Total outer length: 3.600 mm

SKU: 11193

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: length of the tank without cooling unit = 2950mm; Condition of the agitator is unknown, the cooling unit does not work,; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 2580

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 50 mm

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Isoleringsmaterial: PUR

Ytterbeklädnad: RVS 304

Dimensioner av tank

Mått utlopp till marken: 180 mm

Total höjd: 1.800 mm

Omrörare

Position motor: at the top

Typ av omrörare: tripad

Tjocklek på ytterbeklädnad och isolering

Isoleringsmaterial: PUR

Mer

Isolerad: Ja