

259 liter tank i Syrafast 316



161 000 SEK /st exkl moms

Additional information: Pharmacy; Diameter of hand hole 200 mm; smaller dents in the insulating jacket

Volumetric volume (L): 259 L

Pressure in tank: vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 142 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 18 L

Max Overpressure: 3 Bar

Max. working temperature: 142 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Agitator: yes

Number of revolutions: 71 - 640

Power: 0,34

Internal diameter tank: 690 mm

Outer diameter tank: 830 mm

Cylinder height: 470 mm

Total height of tank: 2.000 mm

SKU: 300052



Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 142 °C

Mobil tank: Nej

Övrig information: Pharmacy; Diameter handhole appr. 200 mm; smaller dents in the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 259

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 470 mm
Invändig diameter: 690 mm
Total höjd: 2.000 mm
Ytterdiameter: 830 mm

Omrörare

Kraft (kW): 0,34
Varvtal: 71 - 640

Mer

Isolerad: Ja