2700 liter tank i Syrafast 316



106 000 SEK /st exkl moms

Additional information: transport tank for viscous gels; Technical drawing includes structural changes
Volumetric volume (L): 2.700 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 0,99 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,50 Bar

Max. temperature (°C): 50 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 90 L
Max Overpressure: 0,50 Bar

Max. working temperature: 50 °C
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 95
Internal diameter tank: 1.500 mm

Outer diameter tank: 1.600 mm
Cylinder height: 1.000 mm
Total height of tank: 2.900 mm
Total outer width: 1.700 mm
Total outer length: 2.300 mm

Empty weight tank: 850

SKU: 390155

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 50 °C
Mobil tank: Nej
Övrig information: transport tank for viscous gels; Technical drawing includes structural changes; we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 0,99 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,50 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2700

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.000 mm
Invändig diameter: 1.500 mm
Total höjd: 2.900 mm
Ytterdiameter: 1.600 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Ja
Vikt: 850