

2700 liter tank i Syrafast 316



105 000 SEK /st exkl moms

Additional information: transport tank for viscous gels; Technical drawing includes structural changes

Volumetric volume (L): 2.700 L

Pressure in tank: vacuum

Max. pressure (Bar): 0,99 Bar

Min. pressure (Bar): 0,50 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 90 L

Max Overpressure: 0,50 Bar

Max. working temperature: 50 °C

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 95

Internal diameter tank: 1.500 mm

Outer diameter tank: 1.600 mm

Cylinder height: 1.000 mm

Total height of tank: 2.900 mm

Total outer width: 1.700 mm

Total outer length: 2.300 mm

Empty weight tank: 850

SKU: 265972

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 50 °C

Mobil tank: Nej

Övrig information: transport tank for viscous gels; Technical drawing includes structural changes; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 0,99 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,50 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2700

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.000 mm
Invändig diameter: 1.500 mm
Total höjd: 2.900 mm
Ytterdiameter: 1.600 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Ja
Vikt: 850