27150 liter tank i Rostfritt 304



197 000 SEK /st exkl moms

Additional information: Seal manufacturing; Dents in the double jacket; heating coil (copper) around the cone bottom; cone height approx. 1.400 mm; 1 crane eye in the upper bottom; footplates partially bent; some residues of previous content
Volumetric volume (L): 27.150 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 3,50 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 145 °C
Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: no
Max Overpressure: 3,50 Bar
Max onderdruk: 1 Bar

Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: cylinder
Outlet of tank: 110
Internal diameter tank: 2.790 mm
Outer diameter tank: 2.930 mm

Cylinder height: 3.450 mm
Total height of tank: 6.650 mm

SKU: 410216

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Max. arbetstemperatur: 145 °C
Mobil tank: Nej
Övrig information: Seal manufacturing; Dents in the double jacket; heating coil (copper) around the cone bottom; cone height approx. 1.400 mm; 1 crane eye in the upper bottom; footplates partially bent ; some
Övrig information2: residues of previous content
Omrörare: Nej
Övertryck: 3,50 Bar
Total urtappning: Nej
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 27150

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 3.450 mm
Invändig diameter: 2.790 mm
Total höjd: 6.650 mm
Ytterdiameter: 2.930 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej