27200 liter tank i Syrafast 316



211 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; Stainless steel 304 upright frame; wall thickness of bottom cylinder segment approx. 6 mm; some residues of previous content; manhole cover plated
Volumetric volume (L): 27.200 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 0,15 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,20 Bar

Max. temperature (°C): 50 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: available
Top: 6,10 mm

Cylinder: 5 mm
Bottom: 6,10 mm
Internal diameter tank: 2.400 mm
Outer diameter tank: 2.400 mm
Cylinder height: 5.400 mm

Total height of tank: 7.150 mm

SKU: 477586

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 50 °C
Mobil tank: Nej
Övrig information: Pharmaceutical Chemistry; Stainless steel 304 upright frame; wall thickness of bottom cylinder segment approx. 6 mm; some residues of previous content;manhole cover plated
Omrörare: Nej
Övertryck: 0,15 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,20 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 27200

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 5.400 mm
Invändig diameter: 2.400 mm
Total höjd: 7.150 mm
Ytterdiameter: 2.400 mm

Tjocklek på tank

Botten: 6,10 mm
Cylinder: 5 mm
Topp: 6,10 mm

Mer

Isolerad: Nej