2740 liter tank i Syrafast 316



136 000 SEK /st exkl moms

Additional information: Biotech; 4 feet bolted to height-adjustable weighing pallet made of stainless steel 304; hand hole DN 200
Volumetric volume (L): 2.740 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 90 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 130 °C
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: available
Top: 7,30 mm
Cylinder: 6 mm

Bottom: 4,30 mm
Internal diameter tank: 1.400 mm
Outer diameter tank: 1.564 mm
Cylinder height: 1.410 mm
Total height of tank: 2.930 mm

Total outer width: 1.650 mm
Total outer length: 2.340 mm

SKU: 571763

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 130 °C
Mobil tank: Nej
Övrig information: Biotech; 4 feet bolted to height-adjustable weighing pallet made of stainless steel 304; hand hole DN 200; we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2740

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.410 mm
Invändig diameter: 1.400 mm
Total höjd: 2.930 mm
Ytterdiameter: 1.564 mm

Tjocklek på tank

Botten: 4,30 mm
Cylinder: 6 mm
Topp: 7,30 mm

Mer

Isolerad: Ja