2740 liter tank i Syrafast 316



70 000 SEK /st exkl moms

Additional information: Lid brim slightly bent in places; fixing screws of the lid segment bent; wall thickness of the hinged segment of the tank lid approx. 2 mm; some residues of previous content
Volumetric volume (L): 2.740 L
Pressure in tank: pressure
Max. temperature (°C): 95 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Volume: 120 L
Max Overpressure: 2,50 Bar
Max. working temperature: 95 °C
Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: yes

Outlet of tank: 50
Top: 3 mm
Cylinder: 4 mm
Bottom: 4,90 mm
Internal diameter tank: 1.130 mm

Outer diameter tank: 1.240 mm
Cylinder height: 2.400 mm
Total height of tank: 3.350 mm
Empty weight tank: 750

SKU: 399080

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 95 °C
Mobil tank: Nej
Övrig information: Lid rim slightly bent in places; Fastening screws of the cover segment are bent; Wall thickness of the hinged segment of the tank cap approx. 2 mm; some residues of previous content
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2740

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Ja
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Dimensioner av tank

Cylinderhöjd: 2.400 mm
Invändig diameter: 1.130 mm
Total höjd: 3.350 mm
Ytterdiameter: 1.240 mm

Tjocklek på tank

Botten: 4,90 mm
Cylinder: 4 mm
Topp: 3 mm

Mer

Isolerad: Nej
Vikt: 750