

2740 liter tank i Syrafast 316



70 000 SEK /st exkl moms

Additional information: Lid brim slightly bent in places; fixing screws of the lid segment bent; wall thickness of the hinged segment of the tank lid approx. 2 mm; some residues of previous content

Volumetric volume (L): 2.740 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 95 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 120 L

Max Overpressure: 2,50 Bar

Max. working temperature: 95 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Outlet of tank: 50

Top: 3 mm

Cylinder: 4 mm

Bottom: 4,90 mm

Internal diameter tank: 1.130 mm

Outer diameter tank: 1.240 mm

Cylinder height: 2.400 mm

Total height of tank: 3.350 mm

Empty weight tank: 750

SKU: 275014

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: Lid rim slightly bent in places; Fastening screws of the cover segment are bent; Wall thickness of the hinged segment of the tank cap approx. 2 mm; some residues of previous content

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2740

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 2.400 mm
Invändig diameter: 1.130 mm
Total höjd: 3.350 mm
Ytterdiameter: 1.240 mm

Tjocklek på tank

Botten: 4,90 mm
Cylinder: 4 mm
Topp: 3 mm

Mer

Isolerad: Nej
Vikt: 750