2750 liter tank i Syrafast 316



159 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; 2 pieces of claws made of Fe (contact surface the other way round with bent steel parts; see photos); further technical documents available; manhole cover plated; Metallic discolouration inside
Volumetric volume (L): 2.750 L
Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 62 L
Max Overpressure: 12 Bar

Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: headside
Outlet of tank: available
Agitator: yes
Number of revolutions: 313

Power: 1,10
Top: 7 mm
Cylinder: 5 mm
Bottom: 5 mm
Internal diameter tank: 1.400 mm

Cylinder height: 1.410 mm
Total height of tank: 3.050 mm

SKU: 442376

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Pharmaceutical Chemistry; 2 support brackets made of Fe (contact surface the other way around with cut off steel parts; see photos); further techn. Documents available; manhole cover plated;Metallic
Övrig information2: discolouration inside; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2750

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.410 mm
Invändig diameter: 1.400 mm
Total höjd: 3.050 mm

Omrörare
Kraft (kW): 1,10
Varvtal: 313

Tjocklek på tank
Botten: 5 mm
Cylinder: 5 mm
Topp: 7 mm

Mer
Isolerad: Nej