

2765 liter tank i Syrafast 316



81 000 SEK /st exkl moms

Additional information: Chemistry; Vessel blasted and primed on the outside; double jacket screwed to the lower base (see photos); 4 claws made of Fe; surface attacked in places on the outside (may require repair); some residues of previous content

Volumetric volume (L): 2.765 L

Pressure in tank: vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 42 L

Max Overpressure: 3 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN80

Agitator: yes

Number of revolutions: 167

Power: 2,60

Top: 9 mm

Cylinder: 7 mm

Bottom: 7 mm

Internal diameter tank: 1.400 mm

Cylinder height: 1.390 mm

Total height of tank: 3.350 mm

SKU: 273685

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Tanks blasted and primed on the outside; Double jacket screwed to the lower bottom (see photos); 4 support brackets made of Fe; external surface damaged in places (possibly in need of

Övrig information2: repair); some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2765

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.390 mm

Invändig diameter: 1.400 mm

Total höjd: 3.350 mm

Omrörare

Kraft (kW): 2,60

Varvtal: 167

Tjocklek på tank

Botten: 7 mm

Cylinder: 7 mm

Topp: 9 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Nej