27800 liter tank i Syrafast 316



219 000 SEK /st exkl moms

Additional information: Solvents; Built according to DIN6618; indicated height is measured excluding screwed measuring devices on top of the manhole; transport dimensions are: 4,5 x 3,35 x 3,35 m
Volumetric volume (L): 27.800 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 0,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,10 Bar

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: no
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: headside
Outer diameter tank: 3.350 mm
Total height of tank: 4.550 mm

SKU: 413366

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: Solvents; Built according to DIN6618; indicated height is measured excluding screwed measuring devices on top of the manhole; transport dimensions are: 4,5 x 3,35 x 3,35 m
Omrörare: Nej
Övertryck: 0,50 Bar
Total urtappning: Nej
Undertryck (vakuum): 0,10 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 27800

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Total höjd: 4.550 mm
Ytterdiameter: 3.350 mm

Mer

Isolerad: Nej