

280 liter tank i Syrafast 316



136 000 SEK /st exkl moms

Additional information: Pharmacy; Air-controlled outlet valve; hand hole diameter 200 mm

Volumetric volume (L): 280 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 17 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 130 °C

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 17

Agitator: yes

Number of revolutions: 0 - 767

Power: 0,37

Internal diameter tank: 590 mm

Outer diameter tank: 720 mm

Total height of tank: 1.700 mm

SKU: 564163

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: Pharmacy; Air-controlled outlet valve; hand hole diameter 200 mm; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 280

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Invändig diameter: 590 mm

Total höjd: 1.700 mm

Ytterdiameter: 720 mm

Omrörare

Kraft (kW): 0,37

Varvtal: 0 - 767

Mer

Isolerad: Ja