280 liter tank i Syrafast 316



136 000 SEK /st exkl moms

Additional information: max. permissible temperature in test certificate: -10/+120° C; container drawing in jpeg. format and installation drawing available
Volumetric volume (L): 280 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 28 L
Max Overpressure: 3 Bar

Max onderdruk: 1 Bar
Max. working temperature: 130 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: available

Agitator: yes
Number of revolutions: 339
Power: 0,55
Internal diameter tank: 740 mm
Outer diameter tank: 900 mm

Cylinder height: 630 mm
Total height of tank: 2.100 mm
Empty weight tank: 450

SKU: 461724

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 130 °C
Mobil tank: Nej
Övrig information: Pharmacy; Max.permissible temperature in the test certificate: -10 / + 120 °C; tank drawing in jpeg format and installation drawing available; we can't give any guarantees about the heating/cooling
Övrig information2: jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3,50 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 280

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 630 mm
Invändig diameter: 740 mm
Total höjd: 2.100 mm
Ytterdiameter: 900 mm

Omrörare
Kraft (kW): 0,55
Varvtal: 339

Mer
Värmeväxlare: RVS 304
Isolerad: Ja
Vikt: 450