

2800 liter tank i Rostfritt 304



143,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: Tank AD-2000 Merkblatt, agitator CE0344 ATEX Ex 2 1/3 G bc T4; hardly ever used; we can't give any guarantees about the agitator

Volumetric volume (L): 2.800 L

Max. density P (kg/m³): 1.400

Pressure in tank: pressure

Max. pressure (Bar): 0,50 Bar

Max. temperature (°C): 90 °C

Material wet parts: SS AISI 304 (V2A)



Model: vertical
Configuration: single-skin

Heat exchanger: no
Insulation: no
Mobile tank: no
Top type: dished
Shape of tank: cylindrical

Bottom type: dished
Total discharge: yes
Fixation points: 3 supports for platform
Fixation point(s): RVS 304
Wet parts agitator(s): SS AISI 304L (V2A)

Suitable for food industry: no
Documents included: yes
Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no

Tank outlet: inside Ø 50 mm
Agitator: yes
Position engine: at the top
Number of revolutions: 120
Power: 2,20

Voltage: 400 V - three-phase
Top: 5 mm
Cylinder: 3 mm
Bottom: 3 mm
Internal diameter tank: 1.400 mm

Outer diameter tank: 1.700 mm
Cylinder height: 1.700 mm
Total height of tank: 3.300 mm
Empty weight tank: 750

SKU: 295445

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: single-skin

Max. arbetstemperatur: 90 °C

Maximal densitet för produkten: 1400

Mobil tank: Nej

Övrig information: Tank AD-2000 Merkblatt, agitator CE0344 ATEX Ex 2 1/3 G bc T4; hardly ever used; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 0.50 Bar

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 2800

Utrustning

Dokument finns: Ja

Fläns för omrörare: Nej

Märkskylt: Ja

Tankutlopp: inside Ø 50 mm

Teknisk ritning finns: Ja

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Material vätskeberörd del på omrörare: SS AISI 304L (V2A)

Dimensioner av tank

Cylinderhöjd: 1.700 mm

Invändig diameter: 1.400 mm

Total höjd: 3.100 mm

Ytterdiameter: 1.700 mm

Omrörare

Kraft (kW): 2,20

Position motor: at the top

Varvtal: 120

Spänning (Volt): 400 V – three-phase

Tjocklek på tank

Botten: 3 mm

Cylinder: 3 mm

Topp: 5 mm

Mer

Isolerad: Nej

Vikt: 750