2800 liter tank i Syrafast 316



81 000 SEK /st exkl moms

Additional information: Chemistry; Tank blasted and primed on the outside; 4 support brackets made of Fe; external surface damaged in places (possibly in need of repair); 1 tank with flange-mounted outlet fitting (the spout of this tank is slightly bent); some residues of previous content
Volumetric volume (L): 2.800 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 6 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN80
Agitator: yes
Number of revolutions: 211

Power: 5
Top: 8 mm
Cylinder: 7 mm
Bottom: 6 mm
Internal diameter tank: 1.400 mm

Cylinder height: 1.400 mm
Total height of tank: 3.450 mm

SKU: 397832

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Chemistry; Tank blasted and primed on the outside; 4 support brackets made of Fe; external surface damaged in places (possibly in need of repair); 1 tank with flange-mounted outlet fitting (the
Övrig information2: spout of this tank is slightly bent); some residues of previous content; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 6 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2800

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.400 mm
Invändig diameter: 1.400 mm
Total höjd: 3.450 mm

Omrörare
Kraft (kW): 5
Varvtal: 211

Tjocklek på tank
Botten: 6 mm
Cylinder: 7 mm
Topp: 8 mm

Mer
Isolerad: Nej