

2800 liter tank i Syrafast 316



81 000 SEK /st exkl moms

Additional information: Chemistry; Tank blasted and primed on the outside; 4 support brackets made of Fe; external surface damaged in places (possibly in need of repair); 1 tank with flange-mounted outlet fitting (the spout of this tank is slightly bent); some residues of previous content

Volumetric volume (L): 2.800 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN80

Agitator: yes

Number of revolutions: 211

Power: 5

Top: 8 mm

Cylinder: 7 mm

Bottom: 6 mm

Internal diameter tank: 1.400 mm

Cylinder height: 1.400 mm

Total height of tank: 3.450 mm

SKU: 273721

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Chemistry; Tank blasted and primed on the outside; 4 support brackets made of Fe; external surface damaged in places (possibly in need of repair); 1 tank with flange-mounted outlet fitting (the

Övrig information2: spout of this tank is slightly bent); some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2800

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.400 mm
Invändig diameter: 1.400 mm
Total höjd: 3.450 mm

Omrörare

Kraft (kW): 5
Varvtal: 211

Tjocklek på tank

Botten: 6 mm
Cylinder: 7 mm
Topp: 8 mm

Mer

Isolerad: Nej