28100 liter tank i Syrafast 316



190 000 SEK /st exkl moms

Additional information: Vessel with dents in the cylinder (vacuum damage; see photos); diameter manhole cylinder approx. 600 mm; base ends cut off; 3 dip pipes inside the tank; specified total height incl. connection ring pipe in the upper bottom; outlet with flanged reducing valve; some residues of previous content
Volumetric volume (L): 28.100 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: pressure
Max. pressure (Bar): 1 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN100
Top: 5 mm
Cylinder: 5 mm

Bottom: 8 mm
Internal diameter tank: 2.600 mm
Cylinder height: 4.594 mm
Total height of tank: 7.700 mm

SKU: 475993

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Chemistry; Tank with dents in the cylinder (vacuum damage; see photos); cylinder manhole diameter approx. 600 mm; feet ends cut off; 3 immersion pipes inside the tank; specified total height
Övrig information2: including ring line connection in the upper bottom; outlet with flanged, reducing fitting; some residues of previous content
Omrörare: Nej
Övertryck: 1 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 28100

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 4.594 mm
Invändig diameter: 2.600 mm
Total höjd: 7.700 mm

Tjocklek på tank
Botten: 8 mm
Cylinder: 5 mm
Topp: 5 mm

Mer
Isolerad: Nej