

## 288 liter tank i Syrafast 316



**88,000,00 SEK /st exkl moms**

**Additional information:** Heating of the double jacket by 4 electric screw-in heating elements (4.5 kW each);  
1 screwed-on fitting on the spout; diameter of hand hole 150 mm

**Volumetric volume (L):** 288 L

**Pressure in tank:** pressure

**Max. pressure (Bar):** 2,50 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 125 L

**Max Overpressure:** 2 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** DN25 DIN 11851

**Agitator:** yes

**Number of revolutions:** 91 - 640

**Power:** 0,37

**Internal diameter tank:** 790 mm

**Outer diameter tank:** 950 mm

**Cylinder height:** 500 mm

**Total height of tank:** 2.050 mm

**SKU:** 579842

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Heating of the double jacket by 4 electric screw-in heating elements (4.5 kW each); 1 screwed-on fitting on the spout; diameter of hand hole 150 mm; we can't give any guarantees about the

Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 2,50 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 288

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

## **Dimensioner av tank**

Cylinderhöjd: 500 mm  
Invändig diameter: 790 mm  
Total höjd: 2.050 mm  
Ytterdiameter: 950 mm

## **Omrörare**

Kraft (kW): 0,37  
Varvtal: 91 - 640

## **Mer**

Isolerad: Ja