

2900 liter tank i Rostfritt 304



95 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: dent in the ornamental mantle; we can't give any guarantees about the agitator

Volumetric volume (L): 2.900 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes



Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 3 adjustable feet

Insulation material: Rockwool

Spray ball: RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Valve: RVS 304

Gasket shut-off valve (mat): unknown

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 450 mm

Hinged lid: yes

Tank outlet: inside Ø 45 mm

Total outlet valve: no, optional

Agitator: yes

Agitator type: gate

Position engine: at the top

Insulation body: yes

Insulation thickness: 140

Internal diameter tank: 1.800 mm

Distance from outlet to ground: 360 mm

Outer diameter tank: 2.000 mm

Cylinder height: 1.160 mm

Total height of tank: 2.950 mm

SKU: 192635

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: dent in the ornamental mantle; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 2900

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Tankutlopp: inside Ø 45 mm

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Isoleringsmaterial: Rockwool

Dimensioner av tank

Cylinderhöjd: 1.160 mm

Invändig diameter: 1.800 mm

Mått utlopp till marken: 360 mm

Total höjd: 2.950 mm

Ytterdiameter: 2.000 mm

Omrörare

Position motor: at the top

Typ av omrörare: gate

Tjocklek på ytterbeklädnad och isolering

Isolering mantel: Ja

Isoleringsmaterial: Rockwool

Mer

Isoleringstjocklek OW: 140

Isolerad: Ja