

2900 liter tank i Syrafast 316



214,000,00 kr /st exkl moms

Additional information: Cosmetics; 4 support brackets, stainless steel; Total height is estimated; 1 heating connection cut off; slight metallic discoloration inside the tank

Volumetric volume (L): 2.900 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 110 L

Max Overpressure: 4 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 65

Agitator: yes

Number of revolutions: 960

Power: 4

Top: 6,70 mm

Cylinder: 4,80 mm

Bottom: 4,50 mm

Internal diameter tank: 1.650 mm

Outer diameter tank: 1.800 mm

Cylinder height: 900 mm

Total height of tank: 2.600 mm

SKU: 434261

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Cosmetics; 4 support brackets, stainless steel; Total height is estimated; 1 heating connection cut off; slight metallic discoloration inside the tank; we can't give any guarantees about the

Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2900

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 900 mm

Invändig diameter: 1.650 mm

Total höjd: 2.600 mm

Ytterdiameter: 1.800 mm

Omrörare

Kraft (kW): 4

Varvtal: 960

Tjocklek på tank

Botten: 4,50 mm

Cylinder: 4,80 mm

Topp: 6,70 mm

Mer

Isolerad: Ja