

## 2900 liter tank i Syrafast 316



**211 000 SEK /st exkl moms**

**Additional information:** Cosmetics; 4 stainless steel claws; total height is estimated; 1 heating connection cut off; slight metallic discoloration inside the tank

**Volumetric volume (L):** 2.900 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 110 L

**Max Overpressure:** 4 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 65

**Agitator:** yes

**Number of revolutions:** 960

**Power:** 4

**Top:** 6,70 mm

**Cylinder:** 4,80 mm

**Bottom:** 4,50 mm

**Internal diameter tank:** 1.650 mm

**Outer diameter tank:** 1.800 mm

**Cylinder height:** 900 mm

**Total height of tank:** 2.600 mm

SKU: 434261

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Cosmetics; 4 support brackets, stainless steel; Total height is estimated; 1 heating connection cut off; slight metallic discoloration inside the tank; we can't give any guarantees about the

Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2900

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 900 mm

Invändig diameter: 1.650 mm

Total höjd: 2.600 mm

Ytterdiameter: 1.800 mm

## Omrörare

Kraft (kW): 4

Varvtal: 960

## Tjocklek på tank

Botten: 4,50 mm

Cylinder: 4,80 mm

Topp: 6,70 mm

## Mer

Isolerad: Ja