2900 liter tank i Syrafast 316



213 000 SEK /st exkl moms

Additional information: 4 stainless steel claws; total height is estimated; 1 heating connection cut off; slight metallic discoloration inside the tank
Volumetric volume (L): 2.900 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 110 L
Max Overpressure: 4 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 65

Agitator: yes
Number of revolutions: 960
Power: 4
Top: 6,70 mm
Cylinder: 4,80 mm

Bottom: 4,50 mm
Internal diameter tank: 1.650 mm
Outer diameter tank: 1.800 mm
Cylinder height: 900 mm
Total height of tank: 2.600 mm

SKU: 434261

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Cosmetics; 4 support brackets, stainless steel; Total height is estimated; 1 heating connection cut off; slight metallic discoloration inside the tank; we can't give any guarantees about the
Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2900

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 900 mm
Invändig diameter: 1.650 mm
Total höjd: 2.600 mm
Ytterdiameter: 1.800 mm

Omrörare
Kraft (kW): 4
Varvtal: 960

Tjocklek på tank
Botten: 4,50 mm
Cylinder: 4,80 mm
Topp: 6,70 mm

Mer
Isolerad: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se