29000 liter tank i Syrafast 904L



382 000 SEK /st exkl moms

Additional information: Manhole approx. 500 x 400 mm; if necessary, 1 guardrail could be included (the specified total height does not include the guardrail); 1 load cell under each tank foot (the load cells are missing on one tank); different outlet designs; small cracks in the insulation jacket are possible
Volumetric volume (L): 29.000 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 90 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: cylinder
Outlet of tank: 50
Agitator: yes
Number of revolutions: 15 / 31
Power: 1.1 / 2.2

Top: 4 mm
Cylinder: 3 mm
Bottom: 4 mm
Internal diameter tank: 3.000 mm
Outer diameter tank: 3.140 mm

Cylinder height: 4.000 mm
Total height of tank: 7.700 mm

SKU: 703271

Mer information

Beskrivning av produkt

Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Max. arbetstemperatur: 90 °C
Mobil tank: Nej
Övrig information: Food; Manhole diameter: approx. 530 x 430 mm; dimensions as shown in the drawing; total height excluding the agitator; we can't give any guarantees about the agitator
Övrig information2: one tank); different outlet designs; small cracks in the insulation jacket are possible; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316L (V4A)
Volym i liter: 29000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Dimensioner av tank

Cylinderhöjd: 4.000 mm
Invändig diameter: 3.000 mm
Total höjd: 5.975 mm
Ytterdiameter: 3.140 mm

Omrörare

Kraft (kW): 1.1 / 2.2
Varvtal: 17 / 35

Tjocklek på tank
Botten: 4 mm
Cylinder: 3 mm
Topp: 4 mm

Mer
Isolerad: Ja