

2911 liter tank i Syrafast 316



259,000,00 kr /st exkl moms

Additional information: Cosmetics; Vessel lid can be lifted with lifting frame; Vessel stands on 2 feet and is also attached to the lifting frame; Total height indicated is estimated; Manhole diameter approx. 440 mm; 1 heating connection cut off; 1 dirt protection collar around the outside of the vessel (diameter approx. 1,870 mm)



Volumetric volume (L): 2.911 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 138 °C

Material wet parts: SS AISI 316 (V4A)

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 108 L

Max Overpressure: 5 Bar

Max onderdruk: 1 Bar

Max. working temperature: 151 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Agitator: yes

Number of revolutions: 6.5 - 40

Power: 15

Internal diameter tank: 1.520 mm

Outer diameter tank: 1.740 mm

Cylinder height: 1.130 mm

Total height of tank: 4.300 mm

SKU: 314037

Mer information

Beskrivning av produkt

Material: Syrafast 316

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 138 °C

Mobil tank: Nej

Övrig information: Cosmetics; Vessel lid can be lifted with lifting frame; Vessel stands on 2 feet and is also attached to the lifting frame; Total height indicated is estimated; Manhole diameter approx. 440 mm; 1

Övrig information2: heating connection cut off; 1 dirt protection collar around the outside of the vessel (diameter approx. 1,870 mm)

Omrörare: Ja

Övertryck: 0.25 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2911

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.130 mm

Invändig diameter: 1.520 mm

Total höjd: 4.300 mm

Ytterdiameter: 1.740 mm

Omrörare

Kraft (kW): 15

Varvtal: 6.5 – 40

Mer

Isolerad: Ja